

SAVEMA 20 i&c&tr SERIES THERMAL TRANSFER OVERPRINTERS

32*50 I
53*50 I
32 C



Common Specifications for All Printers

Software: SAYASIS Template Design (Date and Time, Custom Formatted Date and Time, Text, Text Block, Merge Fields, Database Support, Counter, Logo, 1D / 2D Barcodes, GS-1 Barcodes, Table Creation Support and User-Friendly Interface)

Windows Driver Support, Teklynx Software (Code-soft, Labelview and Label Matrix Support), Emulator Support, Printer Management with SPPL (Savema Protocol) Commands, Printer Control with Remote Control)

Barcodes: 1D Barcodes (EAN-13, EAN-8, CODE 128, CODE 39, CODABAR, ITF 2of5, ITF 14, UPC-A, UPC-E ...), 2D Barcodes (Datamatrix, QR Code, PDF417, Aztec code...), GS-1 Barcodes (GS1-128, GS1-Datamatrix, GS1-Databar Barcodes)

Resolution: 300dpi (12 dots/mm) horizontally and vertically

Operating Temperature: 1 °C - 55 °C (34°F-131°F)

Memory: 5000 Template Storage Capacity, 1GB Internal Memory, Up to 16GB SD Memory Card Support, Up to 32GB USB Memory Support



Specifications	32*50 I (Intermittent)	53*50 I (Intermittent)	32 C (Continuous)
Print Area	32 mm x 50 mm	53 mm x 50 mm	32 mm x 50 mm
Print Speed	50 - 400 mm/sec	50 - 400 mm/sec	10 - 550 mm/sec
Production	320 prints/min		500 prints/min
Ribbon Widths & Length	22mm, 35 mm (0,9" - 1,4") & 600 meters (656yards) loaded ribbon	35mm, 55 mm (1,4" - 2,2") & 600 meters (656yards) loaded ribbon	22mm, 35 mm (0,9" - 1,4") & 600 meters (656yards) loaded ribbon
Power Supply	100-240V 50-60 Hz		
Air Supply (Bar)	Min. 1 bar - Max. 5 bar		
Input/Outputs	Print Signal/Fault Signal, Busy Signal		
Output Messages	Update Error, Contact Error, Ribbon Break / Not Found Error, Remaining Ribbon Quantity, Number of Printed Templates, Number of Prints per Minute	Missing Print Error, Encoder Error, Update Error, Contact Error, Ribbon Break / Not Found Error, Remaining Ribbon Quantity, Number of Printed Templates, Number of Prints per Minute	
Connection Types	Relay(NPN, PNP) - Photocell(NPN, PNP)		
Communications	RS-232, Ethernet, USB		
Ribbon Save Modes	Vertical and Horizontal Ribbon Save Modes		Vertical Ribbon Save Mode
Advanced Control	4.3" Touch Screen Control, Template Changing while Running, Print Position Adjustment, Contrast, Print Delay, Template-Specific Adjustment, Internal Contact Signal, Multi-print Contact Signal, Template Shifting, Template Rotation		4.3" Touch Screen Control, Template Changing while Running, Contrast, Print Delay, Template-Specific Adjustment, Internal Contact Signal, Multi-print Contact Signal, Template Shifting, Template Rotation
Operator Interface	4.3" 272x480 pixels resolution, Full-color display, Password protection on menus, Multi-language(18) support		
Weight (Printer)	5,6 Kg.		5,1 Kg.
Dimensions	175mm H x 190mm W x 197mm D	175mm H x 190mm W x 210mm D	175mm H x 190mm W x 197mm D

